

## Terminales autocontraíbles para cable seco unipolar, 15 kV

(mm <sup>2</sup> )	Calibre	AWG	Exterior Autocontraíbles		Interior Autocontraíbles	
			QT II	QT III	QT II	QT III
25	4		5633KC-25	7692-S-4-C25	5623KC-25	7622-T-C25
35	2		5633KC-35	7692-S-4-C35	5623KC-35	7622-T-C35
50	1/0		5633KC-50	7692-S-4-C50	5623KC-50	7622-T-C50
70	2/0		5633KC-70	7692-S-4-C70	5623KC-70	7622-T-C70
95	-		5633KC-95	7692-S-4-C95	5623KC-95	7622-T-C95
120	250		5635KC-120	7694-S-4-C120	5624KC-120	7624-T-C120
150	300		5635KC-150	7694-S-4-C150	5624KC-150	7624-T-C150
185	350		5635KC-185	7694-S-4-C185	5624KC-185	7624-T-C185
240	500		5635KC-240	7694-S-4-C240	5624KC-240	7624-T-C240
300	600		5636KC-300	7695-S-4-C300	5625KC-300	7625-T-C300
500	1000		----	7695-S-4-C500	5625KC-500	7625-T-C500

## Terminales autocontraíbles para cable seco unipolar, 25 kV

(mm <sup>2</sup> )	Calibre	AWG	Exterior Autocontraíbles	Interior Autocontraíbles
			QT III	QT III
35	2		7692-S-4-C35	7693-T-C35
50	1/0		7693-S-4-C50	7693-T-C50
70	2/0		7693-S-4-C70	7693-T-C70
95	--		7693-S-4-C95	7693-S-4-C95
120	250		7695-S-4-C120	7695-T-C120
150	300		7695-S-4-C150	7695-T-C-150
185	350		7695-S-4-C185	7695-T-C185
240	500		7695-S-4-C240	7695-T-C240
300	600		7695-S-4-C300	7695-T-C300
500	1000		7696-S-4-C500	7696-T-C500

## Terminales autocontraíbles para cable seco unipolar, 35 kV

(mm <sup>2</sup> )	Calibre	AWG	Exterior/Interior Autocontraíbles
			QT III
35	2		7684-S-8-C35
50	1/0		7684-S-8-C50
70	2/0		7684-S-8-C70
95	--		7694-S-8C95
120	250		7685-S-8-C120
150	300		7684-S-8-C150
185	350		7685-S-8-C185
240	500		7685-S-8-C240
300	600		7685-S-8-C300
500	1000		7686-S-8-C500

**Nota:** Para diseños de cables tripolares agregar una T. Por ejemplo: QTII 5633KTC-70, QTIII 7692-S-4-T-C35.  
Para otros calibres, sírvase consultarnos.