

PRODUCT-DETAILS

OT630E03CP

OT630E03CP CHANGE-OVER SWITCH



General Information	
Extended Product Type	OT630E03CP
Product ID	1SCA022785R6050
EAN	6417019255965
Catalog Description	OT630E03CP CHANGE-OVER SWITCH
Long Description	Including a black plastic IP65 I-0-II pistol type handle (see the table below), shaft and bolt set for the cable connection. Handle padlockable in the 0-position, door interlock in the I- and lipositions and when padlocked.

Popular Downloads	
Data Sheet, Technical Information	1SCC303003C0201
Instructions and Manuals	1SCC301043M0003

Dimensions	
Product Net Width	311 mm
Product Net Height	250 mm
Product Net Depth / Length	280 mm
Product Net Weight	15.37 kg
	33.89 lb

Technical	
Rated Operational	(380 415 V) 630 A
Current AC-21A (I _e)	(500 V) 630 A
	(690 V) 630 A
Rated Operational	(380 415 V) 630 A
Current AC-22A (I _e)	(500 V) 630 A
	(690 V) 630 A
Rated Operational	(380 415 V) 630 A
Current AC-23A (I _e)	(500 V) 630 A
	(690 V) 630 A
Rated Operational	(380 415 V) 630 A
Current AC-31B (I _e)	(222 4471)
Rated Operational Current AC-33B (I _e)	(380 415 V) 630 A
* **	(200 45.0) 255.10
Rated Operational Power AC-23A (P _e)	(380 415 V) 355 kW (500 V) 400 kW
AC-23A (Pe)	(500 V) 400 kW (690 V) 630 kW
Conventional Free-air	q = 40 °C 630 A
Thermal Current (I _{th})	q-40 C 030 P
Conventional Thermal	Fully Enclosed 630 A
Current (I _{the})	Tally Efficiosed 636 P
Rated Impulse	12 kV
Withstand Voltage (U _{imp}	IL IV
)	
Rated Insulation Voltage	1000 V
(U _i)	
Rated Operational	1000 V
Voltage	
Rated Short-time	for 1 s 20 kiloampere rms
Withstand Current (I _{cw})	
Power Loss	25 W
Pollution Degree	3
Handle Color	Black
Handle Type	Handle and shaft included
Switches Operating	Mechanism at the End of the Switch
Mechanism	03 (Left Side)
Distance Between	Standard
Phases	
Position of Line	Top In - Bottom Out, Bottom In - Top Out
Terminals	
Operating Mode	Front operated
Mounting Type	Base mounting
Number of Poles	3
Degree of Protection	Front IP20
Terminal Width	40 mm
Tightening Torque	acc. IEC 60947-1 50 75 N·m

Environmental

Environmental	1SCC303050D0201
Information	

Certificates and Declarations (Document Number)	
Declaration of Conformity - CE	1SCC303008D0202
Environmental Information	1SCC303050D0201
Instructions and Manuals	1SCC301043M0003
RoHS Information	1SCC301149D0202

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Width	310 mm 12.2 in
Package Level 1 Depth / Length	560 mm 22.05 in
Package Level 1 Height	330 mm 12.99 in
Package Level 1 Gross Weight	18.51 kg 40.81 lb
Package Level 1 EAN	6417019255965

Classifications	
Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnector
ETIM 6	EC000216 - Switch disconnector
ETIM 7	EC000216 - Switch disconnector
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switches \rightarrow Change-over\ and\ Transfer\ Switches \rightarrow Manual\ Change-over\ Switches$

