

Product details page



DPX3 250 LEGRAND

Int. termomagnético DPX3 630 4P, reg de 320A a 400A, 36KA - 380/415Vac

REF. 422007 | CÓDIGO DE BARRAS. 3414970378033

> [Visite nuestro E-catálogo](#)

Características del producto:

- Breakink capacity of 50kA, according to EN/IEC standard 60947-2, suitable for protection of commercial and middle power installations. Rated insulation voltage of 500V. Rated impulse withstand voltage of 6kV.
- Compliant with NEMA AB-1. Climatic condition according to IEC/EN 60947-1 Annex Q, Cat. F subject to temperature, humidity, vibration, shock and salt mist.
- Protection unit with LCD screen for regulation of thermal and magnetic currents. Thermal protection within range of 0,4-1,0 of the rated current. Magnetic protection within range of 1,5-10 of the rated current. Equipped with earth leakage module with LCD screen. Earth leakage trip integrated of type A, with adjustable sensitivity of 0.03 - 0.3 - 1 - 3 Ampere and adjustable tripping of 0 - 0.3 - 1 - 3 seconds
- Can be equipped with releases (undervoltage and shunt releases) and auxiliary contacts. Can used with rotary handles or motor operator. Locking accessories are available.
- Has different type of possible connection accessories: cage terminals, spreader and rear terminals. Is available also in a plug-in version (circuit breaker fitted with special terminals and mounted on a plug-in base)

Intensidad nominal permanente I _u	400 A
Tensión nominal	220-690 V
Corriente nominal de cortocircuito en la corriente de corte I _{cu} a 50 Hz 400 V	36 kA
Ajuste actual de liberación de sobrecarga	320-400 A
Rango de ajuste de liberación instantánea de cortocircuito	2000-4000 A
Construcción del dispositivo	Técnica integrada fija para dispositivo integrado
Protección de fallo a tierra integrada	No
Tipo de conexión del circuito de corriente principal	Conexión roscada
Apto para montaje en carril DIN	No
Montaje en rail DIN opcional	No

Número de contactos auxiliares como contacto de cambio	2
Con alarma activada	Si
Con liberación de baja tensión integrada	Si
Número de polos	4
Posición de la conexión para el circuito principal de tensión	Parte frontal
Ejecución del elemento accionador	Maneta
Aparato completo con dispositivo de protección	Si
Accionamiento motorizado integrado	No
Accionamiento motorizado opcional	Si
Clase de protección (IP)	IP30

Documentación:


Documentación Técnica

 LE07062AB.pdf | PDF (0.81Mo)

Acuerdos y certificados

 LGRP-00702-V01.01-EN.pdf | PDF (1.02Mo)

Especificaciones CAD y de diseño / BIM

 422009.dwg | DWG (0.18Mo)