

# Product details page



## DX3 LEGRAND

Int. Termomagnético DIN DX3 6000 C2, 2X2A, IEC 60947, 25ka/230Vac - 10ka/400Vac

REF. 407793 | CÓDIGO DE BARRAS. 3245064077934

> [Visite nuestro E-catálogo](#)

## Características del producto:

- Breaking capacity 6000A according to IEC 60898-1 standard for household installations. Tripping threshold in case of short-circuit between 10A and 20A (C curve between 5 In and 10 In)
- Can be supplied either by copper cable, prong busbar (top side or bottom side), fork busbar (bottom side) or Legrand HX3 plug busbar (top side).
- Protected against solid bodies larger than 12,5mm ("fingerproof"): IP20 according to IEC/EN 60529 standard. Maximum level of limitation of the let through energy (energy limitation class 3 according to IEC 60898-1 standard).
- Can be equipped with Legrand DX3 auxiliaries, RCD add-on modules and accessories. Can be connected to aluminium cable with terminal accessory n° 4 063 10.
- This device complies with substance-restriction requirements and has been designed in an environmentally conscious process.

## Documentación:

### Especificaciones CAD y de diseño / BIM

 407279.dwg | DWG (0.17Mo)

### Acuerdos y certificados

 AENOR-030/002456 | (0.85Mo)

 LGRP-01959-V01.01-EN.pdf | PDF (0.79Mo)