

# Product details page



## DX3 LEGRAND

Int. Termomagnético DIN DX3 6000 D20, 3X20A, IEC 60947, 25ka/230Vac - 10ka/400Vac

REF. 408090 | CÓDIGO DE BARRAS. 3245064080903

> [Visite nuestro E-catálogo](#)

## Características del producto:

- Breaking capacity 6000A according to IEC 60898-1 standard for household installations. Tripping threshold in case of short-circuit between 200A and 280A (D curve between 10 In and 14 In)
- Can be supplied either by copper cable, prong busbar (top side or bottom side), fork busbar (bottom side) or Legrand HX3 plug busbar (top side).
- Protected against solid bodies larger than 12,5mm ("fingerproof"): IP20 according to IEC/EN 60529 standard.
- Can be equipped with Legrand DX3 auxiliaries, RCD add-on modules and accessories. Can be connected to aluminium cable with terminal accessory n° 4 063 10.
- This device complies with substance-restriction requirements and has been designed in an environmentally conscious process.

## Documentación:

### Especificaciones CAD y de diseño / BIM



407829.dwg | DWG (0.19Mo)

### Acuerdos y certificados



AENOR-030/002456 | (0.85Mo)



LGRP-01959-V01.01-EN.pdf | PDF (0.79Mo)